



StatCare Remover STRIPPING SOLUTION

PRODUCT DESCRIPTION

Our most effective stripper, StatCare Remover rapidly dissolves multiple layers of floor finish, allowing in some applications for removal without the use of floor machines or stripping pads. Formulated almost completely from top quality water miscible solvents, StatCare Remover contains less than 1% solids at concentration, so it leaves no alkaline residue to adversely effect subsequent finish applications. Routine stripping of three to five layers of finish may be accomplished with nothing more than a mop and wet vacuum. No other stripper can surpass StatCare Remover for the removal of heavy build-ups of today's UHS and urethane fortified finishes. Years of buildup can be quickly and easily removed by light agitation with a scrubbing machine and standard stripping pad. StatCare Remover will even dissolve almost impossible to remove straight acrylic sealers. Formulated for those floorcare professionals whose time is at a premium, StatCare Remover is unrivaled in performance and value.

APPLICATION & MAINTENANCE

Dilute 32 ounces of StatCare Remover for routine stripping, 42 ounces for medium build-up, or 128 ounces for heavy build-up per gallon of "warm" water. Apply stripping solution with a mop, and let it stand for five minutes. Remove the dissolved finish and solution with a wet vacuum. Any residual dissolved floor finish not removed by vacuuming should be removed by light rinsing or damp mopping. Allow the floor to dry thoroughly before applying any of StaticSmart's high quality finishes.

StatCare Remover is not recommended for use on Asphalt Tile or older Linoleum Tiles, as it may remove the dye particularly from dark colored tiles.

SAFETY INFORMATION

Health	2
Flammability	0
Reactivity	0
Personal Protection	B

CAUTION: This product contains a strong alkaline ingredient. If ingested, give vinegar, juice of a lemon, grapefruit or orange freely. Do NOT induce vomiting. Get immediate medical attention. If contact with skin or eyes occurs, flush with large volumes of water. **Get immediate medical attention.** Contains 2-BUTOXYETHANOL CAS #111-76-2, ETHANOLAMINE CAS #141-43-5. For detailed information, consult MSDS sheet.

Julie Industries, Inc.

355 Middlesex Avenue
Wilmington, MA 01887
Ph: 978 988-8802
Fax: 978 988-8803
www.staticsmart.com

SPECIFICATIONS

Active ingredients	Water miscible solvents, amine complexes, alcohol ethoxylates
pH.	12.0 - 12.5
Free Ammonia	None
Free Alkali	0.5%
Free Acid	None
Phosphates	None
Abrasives	None
Color.	Light Yellow
Odor.	Moderate
Solubility in Water	100%
Freeze/Thaw Stability	3 cycles
Shelf Life.	Minimum 1 year (30°F - 125°F)
Flash Point.	Above 200°F
Weight Per Gallon.	8.8
Biodegradable	Yes
Soil Suspension	Excellent