
MATERIAL SAFETY DATA SHEET

SECTION 1 — MATERIAL IDENTIFICATION

PRODUCT NAME: StaticSmart Seal
PRODUCT CLASS: Floor sealer / finish
MANUFACTURED FOR: Julie Industries, Inc.
355 Middlesex Avenue
Wilmington, MA 01887
www.staticsmart.com
TELEPHONE NUMBER: 978-988-8802
EMERGENCY TELEPHONE NUMBER: 800-255-3924 or Poison Center
REVISION DATE: July 2005

SECTION 2 — HAZARDOUS INGREDIENTS

CHEMICAL NAME	CAS Number	PEL ppm	TWA ppm	STEL ppm	%
Not a hazardous mixture, as defined in 29 CFR 1910,1200 and M.G.L. c. 111F					
Contains: GLYCOL ETHERS*					<6
*CHEMICAL CATEGORY SUBJECT TO REPORTING REQUIREMENTS OF SEC.313, TITLE III.					

SECTION 3 — PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT (°F): 218
SPECIFIC GRAVITY (WATER=1): 1.02
VAPOR PRESSURE (mm Hg): 18.0
VAPOR DENSITY (AIR=1): 1.1
VISCOSITY (CPS): 15
pH: 8.6 +/- .5
APPEARANCE AND ODOR: Translucent white liquid
EVAPORATION RATE (Butyl Acetate = 1): 0.36
SOLUBILITY IN WATER: Complete
MELTING POINT: N/A
DECOMPOSITION TEMPERATURE: N/A
AUTO IGNITION TEMP.: N/A

SECTION 4 — FIRE AND EXPLOSION DATA

FLASH POINT (°F):	None
LOWER FLAMMABLE LIMIT:	N/A
UPPER FLAMMABLE LIMIT:	N/A
EXTINGUISHING MEDIA:	N/A
FIRE-FIGHTING PROCEDURE:	N/A
FIRE AND EXPLOSION HAZARDS:	N/A

SECTION 5 — REACTIVITY DATA

CHEMICAL STABILITY:	Stable
CONDITIONS TO AVOID:	Freezing, extreme heat
INCOMPATIBILITY:	Acids, oxidizers
POLYMERIZATION:	Will not occur
HAZARDOUS DECOMPOSITION OR BYPRODUCT:	Thermal decomposition may yield carbon monoxide

SECTION 6 — HEALTH HAZARD DATA

PRIMARY ROUTES OF ENTRY:	No primary routes of entry
MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:	N/A
POTENTIAL HEALTH EFFECTS	
ACUTE:	Causes eye and skin irritation.
CHRONIC:	Redness of skin.
CARCINOGENICITY:	No.
SIGNS AND SYMPTOMS OF EXPOSURE:	Itching, irritating sensation.
N.T.P:	N/A
IARC Monographs:	N/A
OSHA Regulated:	N/A

SECTION 7 — FIRST AID MEASURES

EMERGENCY AND FIRST AID PROCEDURES:	Wash contact areas with soap and water.
INGESTION:	Drink milk, water or citrus juice, induce vomiting with oil of ipecac. Call physician immediately.

SECTION 8 — PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN

IF MATERIAL IS SPILLED OR RELEASED: Dispense sand, sawdust, or vermiculite. Collect and place in plastic waste container. Wash area thoroughly with water.

WASTE DISPOSAL METHOD: Use sanitary landfill disposal, (not a hazardous waste) according to federal, state and local regulations. (RCRA; subtitle D)

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

Do not mix with other chemicals. Store away from heat. Keep from freezing.

OTHER PRECAUTIONS:

KEEP OUT OF THE REACH OF CHILDREN.

SECTION 9 — EXPOSURE CONTROLS/PERSONAL PROTECTION

RESPIRATORY PROTECTION: Not normally required with good ventilation.

VENTILATION: Assure fresh air circulation.

EYE/FACE PROTECTION: Safety glasses recommended.

SKIN PROTECTION: Rubber gloves recommended.

WORK/HYGIENIC PRACTICES: Do not eat or drink next to material, wash hands after working with material.

SECTION 10 — TRANSPORTATION 49 CFR

OSHA: Not regulated

Report Qty (lbs.): N/A

DOT: Not regulated

LABELS: None required

UN: Not regulated

SECTION 11 — OTHER INFORMATION

HMIS RATINGS:

Health: 1

Flammability: 0

Reactivity: 0

Personal Protective Equipment: B

HAZARD RATING SCALE:

0 = Minimal; 1 = Slight; 2 = Moderate; 3 = Serious; 4 = Severe

The product manufacturer believes the statements, technical information and recommendations contained herein are reliable. They are given without warranty or guarantee of any kind, expressed or implied.

Vendor assumes no responsibility for injury to vendee or third person proximately caused if reasonable safety procedures are not adhered to as stipulated in the data sheet. Additionally, vendor assumes no responsibility for injury to vendee or third persons proximately caused by abnormal use of the material even if reasonable safety procedures are followed. Further more, vendee assumes the risk in use of the material.